

IPC10B-5

5MP Smart AI Hybrid Light POE Network Metal Bullet Camera



Model Number	IPC10B-5
Camera	
Image Sensor	1/2.7" 5MP low illumination CMOS sensor
Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Shutter Time	Auto(1/5 - 1/100000)
Lens	
Lens Type	Fixed Lens 3.6mm @F1.6
Lens Resolution	5MP
Illuminator	
Light Distance	Warm Light 30m, IR Light 40m
IR LEDs	3pcs Hybrid Light LEDs
Day & Night Mode	Dual Light Mode: B/W night vision, when alarm triggered hybrid light is on, and then full color vision
	Infrared Mode: B/W
	Full Color: the LEDs will auto-adjust its brightness according to the varying degrees of light brightness
Video	
Max. Image Resolution	5MP(2880*1620)@25fps
Video Compression	S.265/H.265/H.264

Frame Rate	<p>Main stream: PAL: 5MP (2880x1620@25fps),4MP(2560x1440@25fps),3MP(2304x1296@25fps), 2MP(1920x1080@25fps NTSC: 5MP(2880x1620@30fps),4MP(2560x1440@30fps),3MP(2304x1296@30fps), 2MP(1920x1080@30fps</p> <p>Sub-stream: PAL:D1(720x576)@25fps,VGA(640x480)@25fps,Q720P(640x360)@25fps, 864x480@25fps NTSC:D1(720x576)@30fps,VGA(640x480)@30fps,Q720P(640x360)@30fps, 864x480@30fps</p>
Video Bit Rate	1024Kbps-8000Kbps support self-adjustable as needed
Image Settings	Brightness,contrast,saturation,sharpness,chroma
White Balance	Auto / Manual
Gain Control	Support
BLC	Support
HLC	Support
WDR	Digital WDR
Noise Reduction	3D NR(Off/Low/Middle/High/Higher)
Defog	Off/Low/Middle/High
Mirror	Off/horizontal mirror/vertical mirror/180° flip
Character Overlay (OSD)	Title, time and date overlay, multi-line, and color of characters optional
Audio	
Audio Input	Support, built-in microphones
Audio Output	Support, built-in speaker
Voice Broadcast Alarm	Built-in 8 different broadcast options
Audio Compression	G.711U/64Kbps
Network	
Network Interface	1*RJ45 10M/100M Self-adaptation Ethernet Port
Networking Protocol	TCP/IP,UDP,HTTP,HTTPS,DHCP,RTSP
Connection Protocol	Onvif,GB28181
APP(P2P)	Through the NVR
PC	Support
Web Access	Support HTML5 remote login operation(Free plug-in)
Preview Simultaneously Video Number	4
Device Abnormal Inspection	Support network broken alarm, IP conflict alarm, illegal visiting alarm
Security Mode	Authorized user name and password,HTTPS encryption,AES connecting encryption, RTSP verification
Event	

EASY IP Series Network Camera | IPC10B-5

Alarm	Motion Detection Alarm, AI Humanoid Detection and Tracking Alarm
Linkage	Upload to FTP, Upload Picture, send email, trigger recording, trigger capture, Arming time support 24h arming/ night arming /customized arming
Basic Event	
Motion Detection	Set detection area, can set multi-level sensitivity
Occlusion Alarm	Support 1 area
Privacy Mask	Support 4 areas
Smart Event	
Human Detection	It can detect target $\leq 5-10$ persons at the same time
	Humanoid pixel $\geq 40 \times 40$
	Detection Ratio $\geq 99\%$ (meet above requirement)
	Capture Corresponding Speed $\leq 1s$
	Support specified area detection, default full screen
	Error detection rate 2% or less
	Maximum detection frame rate is 5fps /s
Interface	
Ethernet Interface	1 RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	No
Alarm	No
RS-485	No
Generale	
POE	IEEE802.3af
Power Supply	DC12V $\pm 10\%$ /POE
Power Consumption	Max 6W
Lightning Protection	6KV
Housing	Metal Bullet
Weather Proof	IP66
Working Temperature	-10 °C to 50 °C
Working Humidity	10%-95% (Non-condensing)

Dimensioni

